

Crown Bevcan, Europe & Middle East

www.crowncork.com

Status: **Provisional**

Issue Date: **31 May 2017**

Version Number: **P**

Authorised By:

|                                   |                          |
|-----------------------------------|--------------------------|
| Nominal Fill Volume :             | <b>330ml</b>             |
| Container Brimful Capacity :      | <b>359ml +/- 1.8</b>     |
| Individual Axial Load :           | <b>800N min.</b>         |
| Minimum Dome Reversal Pressure :  | <b>6.2bar</b>            |
| Internal Lacquer Specification :  | <b>Water-based Epoxy</b> |
| External Base Protection :        | <b>Single Rim Coat</b>   |
| Nominal Bright Container Weight : | <b>9.5g</b>              |



## Can Specification

| Entity Code | Entity Description          | Value     | Tolerance |
|-------------|-----------------------------|-----------|-----------|
| B           | Inside Neck Diameter        | 52.40 mm  | ±.30      |
| D           | Outside Can Diameter        | 58.00 mm  | max.      |
| E           | Flange Width                | 2.10 mm   | ±.25      |
| Et          | Flange Thickness            | .165 mm   | nom.      |
| F           | Flange Diameter             | 57.32 mm  | max.      |
| H           | Factory Finished Can Height | 145.40 mm | ±.30      |
| HS          | Headspace                   | 12.60 mm  | nom.      |
| J           | Neck Seaming Clearance      | 3.00 mm   | min.      |
| kd          | Stand Diameter              | 46.23 mm  |           |
| N           | Neck Length                 | 10.00 mm  |           |
| rb          | Flange Radius               | 1.52 mm   | nom.      |
| XB          | Flange Angle                | 7.5° max. |           |

